

## CLiQSMART® CM 120

Defoamer/Air-release Agent

**CLiQSMART CM 120** is a dry powder defoamer/air-release agent for mineral-based construction materials. The defoamer is free of VOC and mineral oil.

**CLiQSMART CM 120** has an excellent cost/performance balance. The active defoaming material is finely distributed on the carrier, resulting in highly efficient defoaming with minimal impact on the secondary properties of mineral-based construction systems.

**CLiQSMART CM 120** is a ready-to-use defoamer that can be easily added to the dry mix during production. Its efficiency is developed when the construction system is mixed with water prior to application.

### Typical values:

Appearance:	White powder
pH-value:	ca. 8
Bulk Density:	ca. 450 g/l
Moisture:	5.5%

### Level of Use / Incorporation:

**CLiQSMART CM 120** is added in the standard production process of construction systems. The optimum loading level should be determined for each system using a loading ladder study. A loading between 0.05 – 0.30% based on total is typically required to achieve the desired defoaming efficiency.

**CLiQSMART CM 120** is easy to use and shows minor influence on other system properties. Like other defoamers, it is suggested to evaluate the compatibility of the product in each individual formulation.

**CLiQPERSE CM 120** should be stored in a cool dry place. The minimum shelf life is 12 months when stored in unopened original packages.

For information on health and safety information, please consult the Material Safety Data Sheet.

CLiQ SwissTech AG  
Bahnhofstrasse 3  
7320 Sargans  
Switzerland

CLiQ SwissTech (Deutschland) GmbH  
Bertram-Blank-Strasse 8A  
51427 Bergisch Gladbach  
Germany

CLiQ SwissTech (Netherlands) B.V.  
Blauwborgje 31  
9747AC Groningen  
The Netherlands

sample@cliqswiss.com • info@cliqswiss.com

[www.cliqswiss.com](http://www.cliqswiss.com)

This information is based to best of our knowledge and on test results obtained in our laboratory. It is given in good faith and should only regard as recommendations. No warranty is given, and it is advised to all users to evaluate the products carefully for their intended use. Please also consider all further information, labels, and especially the safety data sheet! For further questions, technical service, and samples, please feel free to contact us.