

# CLiQSMART® HM-2 (LP 2213-1)

Humectant / Wetting Agent

**CLiQSMART HM-2 (LP 2213-1)** is a 100% active non-ionic glycol ether for aqueous applications. The wetting agent is VOC-free and meets strongest VOC-regulation requirements. It is predominately recommended as humectant in aqueous pigment preparations to prevent drying out of the concentrates on tinting machines.

**CLiQSMART HM-2 (LP 2213-1)** by nature is a wetting agent that also wets out pigments and extenders during the incorporation process. Thus, resulting in an improved dispersion process, better system stability and compatibility of e.g. pigment concentrates in paints.

**Typical values:**

Appearance: Clear liquid  
 Active Content: 100%  
 pH-value: 6 - 8

**Level of Use / Incorporation:**

**CLiQSMART HM-2 (LP 2213-1)** is best dissolved in water, prior to pigment addition but also be post added to concentrates.  
 The optimum loading level should be determined for each system using a loading ladder system.

**CLiQSMART HM-2 (LP 2213-1)** should be stored in a cool dry place above 10°C. The material may get hazy and solid at low temperature storage, this does not impact product quality. The minimum shelf life is 36 months when stored in unopened packages.

For information on health and safety information, please consult the Material Safety Data Sheet.

CLiQ SwissTech AG  
 Bahnhofstrasse 3  
 7320 Sargans  
 Switzerland

CLiQ SwissTech (Deutschland) GmbH  
 Bertram-Blank-Strasse 8A  
 51427 Bergisch Gladbach  
 Germany

CLiQ SwissTech (Netherlands) B.V.  
 Blauwborgje 31  
 9747AC Groningen  
 The Netherlands

sample@cliqswiss.com • info@cliqswiss.com

www.cliqswiss.com

This information is based to best of our knowledge and on test results obtained in our laboratory. It is given in good faith and should only regard as recommendations. No warranty is given, and it is advised to all users to evaluate the products carefully for their intended use. Please also consider all further information, labels, and especially the safety data sheet! For further questions, technical service, and samples, please feel free to contact us.