

CLiQSPERSE® BS

Dispersing Agent

CLiQSPERSE BS is a high molecular weight polyester amide based pigment dispersing agent for non-aqueous applications. The modified polyester provides excellent performance to all pigment grades and is used in industrial systems to produce versatile highly concentrated pigment concentrates for full-tone and pastel colours in e.g. coatings application.

CLiQSPERSE BS provides maximum colour strength, gloss retention and excellent colour acceptance in a large variety of non-aqueous systems. It prevents re-flocculation and stabilizes pigments in coatings and pigment concentrates.

CLiQSPERSE BS reduces grinding time and provides a low viscous pigment grind / mill-base. The dispersing and wetting agent does not negatively influence the paint durability due to its high molecular weight structure. It is often used in combination with grinding resin in resin containing pigment concentrates.

Typical values:

Appearance:	Yellowish liquid
Active Content:	>40%
Density:	Ca 1.0 g/cm ³
Solvent:	MPA

Level of Use / Incorporation:

CLiQSPERSE BS is best dissolved in solvents/binder prior to pigment addition. The optimum loading level should be determined for each system using a loading ladder study.

CLiQSPERSE BS can be used alone or in combination with a grinding resin. The following loading levels based on pigment load are recommended as starting point:

Inorganic pigments:	5 - 15 %
Organic pigments:	30 - 60 %
Carbon blacks:	80 - 100%

CLiQSPERSE BS should be stored in a cool dry place. The minimum shelf life is 24 months when stored in unopened packages.

For information on health and safety information please consult the Material Safety Data Sheet.

CLiQ SwissTech AG
Bahnhofstrasse 3
7320 Sargans
Switzerland

CLiQ SwissTech (Deutschland) GmbH
Bertram-Blank-Strasse 8A
51427 Bergisch Gladbach
Germany

CLiQ SwissTech (Netherlands) B.V.
Blauwborgje 31
9747AC Groningen
The Netherlands

sample@cliqswiss.com · info@cliqswiss.com

www.cliqswiss.com

This information is based to best of our knowledge and on test results obtained in our laboratory. It is given in good faith and should only regard as recommendations. No warranty is given, and it is advised to all users to evaluate the products carefully for their intended use. Please also consider all further information, labels, and especially the safety data sheet! For further questions, technical service, and samples, please feel free to contact us.