

CLiQFLOW® 660 VR

Rheological Additive

CLiQFLOW 660 VR is a VOC-compliant, biocide- and organotin-free polyurethane thickener for aqueous decorative and industrial systems. The associative thickener increases both low and mid shear viscosity and provides a shear thinning flow behaviour.

CLiQFLOW 660 VR improves anti-settling behaviour, sag resistance and brush drag of aqueous systems. The associative thickener also provides improved workability with superior flow and levelling that results in a more uniform paint film after application.

CLiQFLOW 660 VR is often used in combination with CLiQFLOW 680 or CLiQFLOW 690 in decorative brush or roller applied paints to achieve an optimised flow and application behaviour.

CLiQFLOW 660 VR is also available in higher concentration with 40 % active.

Typical values:


Appearance:	white opaque liquid
Active Content	ca. 25 %
Brookfield Viscosity:	< 2000 mPas
Density:	ca. 1.05 g/cm ³

Level of Use / Incorporation:

CLiQFLOW 660 VR can be added to the aqueous system at any production stage. It does not require a pre-dilution step.

The optimum loading level with **CLiQFLOW 660 VR** should be determined for each system using a loading ladder study. A loading level between 0.2-2.0 % is recommended.

CLiQFLOW 660 VR shows excellent compatibility with most kind of aqueous binders us used for decorative applications.



CLiQFLOW 660 VR should be stored in a cool dry place above 5°C.

For information on health and safety information please consult the Material Safety Data Sheet

CLiQ SwissTech AG
Bahnhofstrasse 3
7320 Sargans
Switzerland

CLiQ SwissTech (Deutschland) GmbH
Bertram-Blank-Strasse 8A
51427 Bergisch Gladbach
Germany

CLiQ SwissTech (Netherlands) B.V.
Blauwborgje 31
9747AC Groningen
The Netherlands

sample@cliqswiss.com · info@cliqswiss.com

www.cliqswiss.com

This information is based to best of our knowledge and on test results obtained in our laboratory. It is given in good faith and should only regard as recommendations. No warranty is given and it is advised to all users to evaluate the products carefully for their intended use. Please consider also all further information, labels, and especially the safety data sheet! For further questions, technical service and samples, please feel free to contact us.

CLiQ SwissTech AG
Bahnhofstrasse 3
7320 Sargans
Switzerland

CLiQ SwissTech (Deutschland) GmbH
Bertram-Blank-Strasse 8A
51427 Bergisch Gladbach
Germany

CLiQ SwissTech (Netherlands) B.V.
Blauwborgje 31
9747AC Groningen
The Netherlands

sample@cliqswiss.com · info@cliqswiss.com

www.cliqswiss.com

This information is based to best of our knowledge and on test results obtained in our laboratory. It is given in good faith and should only regard as recommendations. No warranty is given and it is advised to all users to evaluate the products carefully for their intended use. Please consider also all further information, labels, and especially the safety data sheet! For further questions, technical service and samples, please feel free to contact us.

Version: 20-Mar-23