

CLiQSMART® PD-20

Defoamer

CLiQSMART PD-20 is a silicone and polymer based defoamer for a large variety of systems based on unsaturated polyester and epoxy resins. It prevents foam formation during production and application.

CLiQSMART PD-20 shows excellent compatibility and efficiency in coatings and ambient cured thermosets based on epoxy and unsaturated polyester resins. The defoamer is also highly recommended for all kind of protective coatings and pultrusion systems based on epoxy resins.

Typical values:

Appearance:	clear liquid
Solids content:	5 %
Density:	ca 0.81 g/cm ³

Level of Use / Incorporation:

CLiQSMART PD-20 is best added to the resin under sufficient mixing. Post addition is possible when adequate shear forces are available to homogenise the material successfully.

CLiQSMART PD-20 is typically added at concentration between 0.2 – 1.0 % as delivered on total formulation. The optimum loading level should be determined for each system using a loading ladder study.

CLiQSMART PD-20 should be stored in a cool dry place.

For information on health and safety information please consult the Material Safety Data Sheet.

CLiQ SwissTech AG
Bahnhofstrasse 3
7320 Sargans
Switzerland

CLiQ SwissTech (Deutschland) GmbH
Bertram-Blank-Strasse 8A
51427 Bergisch Gladbach
Germany

CLiQ SwissTech (Netherlands) B.V.
Blauwborgje 31
9747AC Groningen
The Netherlands

sample@cliqswiss.com · info@cliqswiss.com

www.cliqswiss.com

This information is based to best of our knowledge and on test results obtained in our laboratory. It is given in good faith and should only regard as recommendations. No warranty is given and it is advised to all users to evaluate the products carefully for their intended use. Please consider also all further information, labels, and especially the safety data sheet! For further questions, technical service and samples, please feel free to contact us.

Version: 20-Mar-23