

CLiQSPERSE 125 is a highly efficient multifunctional non-ionic pigment wetting agent for aqueous systems. The additive is applied as replacement to alkylphenol ethoxylate (APE) and used in modern labelling-free VOC-compliant formulations.

CLiQSPERSE 125 is used in both decorative and industrial base paints or pigment concentrates to improve colorant acceptance and tinting strength. It enhances pigment wetting, reduces flooding and floating and to prevents re-flocculation of pigments during storage.

CLiQSPERSE 125 is used in standard latex paints to maintain viscosity on storage and to improve overall stability of aqueous systems.

Typical values:

Appearance:	clear yellow liquid
Solids content:	100 %
Brookfield viscosity:	ca. 2400 mPa.s
Density (20°C):	ca. 1.1 g/cm ³
pH-value:	ca. 6.0

Level of Use / Incorporation:

CLiQSPERSE 125 is best dispersed with pigments and extenders for maximum efficiency. Depending on the pigment nature a loading level between 2 and 15 % is recommended for pigment concentrates. For paint formulations a loading level between 0.1-0.6 % is recommended.

CLiQSPERSE 125 is compatible with most aqueous general industrial and architectural systems based on a variety of binder systems

CLiQSPERSE 125 should be stored in a cool dry place. Closed containers can be stored up to 2 years.

For information on health and safety information please consult the Material Safety Data Sheet.

CLiQ SwissTech AG
Bahnhofstrasse 3
7320 Sargans
Switzerland

CLiQ SwissTech (Deutschland) GmbH
Hauptstrasse 97
51465 Bergisch Gladbach
Germany

CLiQ SwissTech (Netherlands) B.V.
Zernikepark 6-8
9747AN Groningen
The Netherlands

sample@cliqswiss.com • info@cliqswiss.com
www.cliqswiss.com

This information is based to best of our knowledge and on test results obtained in our laboratory. It is given in good faith and should only regard as recommendations. No warranty is given and it is advised to all users to evaluate the products carefully for their intended use. Please consider also all further information, labels, and especially the safety data sheet! For further questions, technical service and samples, please feel free to contact us.

Version: 20130314