

CLiQSPERSE BL is an aromatic-free polymeric pigment dispersing agent for non-aqueous systems. The modified polyurethane is used in industrial base paints and in highly concentrated grinding resin based pigment concentrates.

CLiQSPERSE BL is recommended for all kind of pigments to provide maximum colour strength, gloss retention and excellent colour acceptance in a variety of non-aqueous systems. It prevents re-flocculation and stabilizes pigments in paints and pigment concentrates.

CLiQSPERSE BL reduces grinding time and gives a non-thixotropic low viscous mill-base. The dispersing and wetting agent does not negatively influence the paint durability due to its resin-like high molecular weight structure.

Typical values:

Appearance:	Yellowish liquid
Solids content:	ca. 43 %
Brookfield viscosity :	ca. 500 mPa.s
Density (20°C):	1.0 g/cm ³
Solvents:	MPA / butyl acetate

Level of Use / Incorporation :

CLiQSPERSE BL is best dissolved in solvents prior to pigment addition. The optimum loading level should be determined for each system using a loading ladder study.

CLiQSPERSE BL can be used alone or in combination with a grinding resin. The following loading levels are recommended as starting point:

Inorganic pigments:	10 % of the oil absorption
Organic pigments:	25 - 50 % of BET-value
Carbon blacks:	20 % of the DBP-value

CLiQSPERSE BL is compatible with most industrial non-aqueous based systems like 2c epoxy, 2c polyurethanes, stoving enamels, polyester and alkyd systems.

CLiQSPERSE BL should be stored in a cool dry place. Closed containers can be stored up to 60 months.

For information on health and safety information please consult the Material Safety Data Sheet.

CLiQ SwissTech AG
Bahnhofstrasse 3
7320 Sargans
Switzerland

CLiQ SwissTech (Deutschland) GmbH
Hauptstrasse 97
51465 Bergisch Gladbach
Germany

CLiQ SwissTech (Netherlands) B.V.
Zernikepark 6-8
9747AN Groningen
The Netherlands

sample@cliqswiss.com • info@cliqswiss.com

www.cliqswiss.com

This information is based on best of our knowledge and on test results obtained in our laboratory. It is given in good faith and should only regard as recommendations. No warranty is given and it is advised to all users to evaluate the products carefully for their intended use. Please consider also all further information, labels, and especially the safety data sheet! For further questions, technical service and samples, please feel free to contact us.